


Model N360, LFN360, N360I, LFN360I


Installation Instructions for Water Service

Install Model N360, LFN360, N360I or LFN360I in cold water supply line with or above the highest point in the tank.

Model N360, LFN360 and N360I, LFN360I can be installed either horizontally or vertically as shown. No valve is to be placed between the relief valve and the tank. Illustrations show typical and correct positions. Valve opens on vacuum of not over 1/2" mercury column. Maximum working pressure: 200psi (13.8 bar). (Maximum steam working pressure: 15psi or 103.4 kPa.) Maximum temperature: 250°F (121°C).



Domestic Hot Water Supply Tanks and Heaters with Top Supply



Domestic Hot Water Supply Tanks and Heaters with Bottom Feed




Table Top Heaters

Caution: Not Suitable for Cross-Connection Control.

CALIFORNIA PROPOSITION 65 WARNING
WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. (California law requires this warning to be given to customers in the State of California.)
 For more information: www.watts.com/prop65



A Watts Water Technologies Company



USA: Tel. (978) 688-1811 • Fax: (978) 794-1848 • www.watts.com
 Canada: Tel. (905) 332-4090 • Fax: (905) 332-7068 • www.watts.ca

For Low Pressure Steam Service


Note: When used for Steam Service, BE SURE to use pigtail to prevent live steam from damaging Model N360, LFN360, N360I and LFN360I Valves.

Maximum Steam Pressure: 15psi (103.4 kPa).

Maximum Temperature: 250°F (121°C).



Low Pressure Steam Heating Systems



Limited Warranty: Watts Regulator Co. (the "Company") warrants each product to be free from defects in material and workmanship under normal usage for a period of one year from the date of original shipment. In the event of such defects within the warranty period, the Company will, at its option, replace or recondition the product without charge.

THE WARRANTY SET FORTH HEREIN IS GIVEN EXPRESSLY AND IS THE ONLY WARRANTY GIVEN BY THE COMPANY WITH RESPECT TO THE PRODUCT. THE COMPANY MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED. THE COMPANY HEREBY SPECIFICALLY DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

The remedy described in the first paragraph of this warranty shall constitute the sole and exclusive remedy for breach of warranty, and the Company shall not be responsible for any incidental, special or consequential damages, including without limitation, lost profits or the cost of repairing or replacing other property which is damaged if this product does not work properly, other costs resulting from labor charges, delays, vandalism, negligence, fouling caused by foreign material, damage from adverse water conditions, chemical, or any other circumstances over which the Company has no control. This warranty shall be invalidated by any abuse, misuse, misapplication, improper installation or improper maintenance or alteration of the product.

Some States do not allow limitations on how long an implied warranty lasts, and some States do not allow the exclusion or limitation of incidental or consequential damages. Therefore the above limitations may not apply to you. This Limited Warranty gives you specific legal rights, and you may have other rights that vary from State to State. You should consult applicable state laws to determine your rights. **SO FAR AS IS CONSISTENT WITH APPLICABLE STATE LAW, ANY IMPLIED WARRANTIES THAT MAY NOT BE DISCLAIMED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE LIMITED IN DURATION TO ONE YEAR FROM THE DATE OF ORIGINAL SHIPMENT.**