## INSTALLATION INSTRUCTIONS

# **Series SA-1**

## Water Hammer Arrestors

#### **Installation Instructions**

Shock waves are caused by fast acting valves and can be controlled by using a shock arrestor. Use one unit for each hot and cold water line.


Series SA-1 is designed for new or existing water lines with pressures up to 150psi (10.3 bar) and temperature ranges of 33°F (0.5°C) to 180°F (82°C). Systems which exceed 60psi shall be installed with a pressure reducing valve upstream of the unit.


Select a location as close to the source of shock (i.e. dishwasher, icemaker, toilet or faucet) as possible. Allow sufficient clearance for installation.

For your safety these units are pre-charged at the factory and are not rechargeable or repairable.

Although they function in any orientation, Figure 1 and 2 show the proper installation where the shock would be absorbed most effectively.

Figure 1







#### **CALIFORNIA PROPOSITION 65 WARNING**

**WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. (California law requires this warning to be given to customers in the State of California.)

For more information: www.watts.com/prop65

**Limited Warranty:** FEBCO warrants each product to be free from defects in material and workmanship under normal usage for a period of one year from the date of original shipment. In the event of such defects within the warranty period, the Company will, at its option, replace or recondition the product without charge.

THE WARRANTY SET FORTH HEREIN IS GIVEN EXPRESSLY AND IS THE ONLY WARRANTY GIVEN BY THE COMPANY WITH RESPECT TO THE PRODUCT. THE COMPANY MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED. THE COMPANY HEREBY SPECIFICALLY DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

The remedy described in the first paragraph of this warranty shall constitute the sole and exclusive remedy for breach of warranty, and the Company shall not be responsible for any incidental, special or consequential damages, including without limitation, lost profits or the cost of repairing or replacing other properly, which is damaged if this product does not work properly, other costs resulting from labor charges, delays, vandalism, negligence, fouling caused by foreign material, damage from adverse water conditions, chemical, or any other circumstances over which the Company has no control. This warranty shall be invalidated by any abuse, misuse, misapplication, improper installation or improper maintenance or alteration of the product.

Some States do not allow limitations on how long an implied warranty lasts, and some States do not allow the exclusion or limitation of incidental or consequential damages. Therefore the above limitations may not apply to you. This Limited Warranty gives you specific legal rights, and you may have other rights that vary from State to State. You should consult applicable state laws to determine your rights. SO FAR AS IS CONSISTENT WITH APPLICABLE STATE LAW, ANY IMPLIED WARRANTIES THAT MAY NOT BE DISCLAIMED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE LIMITED IN DURATION TO ONE YEAR FROM THE DATE OF ORIGINAL SHIPMENT.



ISO 9001-2000 CERTIFIED

A Division of Watts Water Technologies, Inc.

USA: 4381 N. Brawley • Ste. 102 • Fresno, CA • 93722

- Tel. (559) 441-5300 Fax: (559) 441-5301 www.FEBCOonline.com Canada: 5435 North Service Rd. • Burlington, ONT. • L7L 5H7
- Tel. (905) 332-4090 Fax: (905) 332-7068 www.FEBCOonline.ca

IS-F-SA-1 0845 EDP# 1915960 © FEBCO, 2008

1-A2-7-SI

## INSTALLATION INSTRUCTIONS

# **1-A2 saira2**

## Water Hammer Arrestors

## Installation Instructions

Use one unit for each hot and cold water line. Shock waves are caused by fast acting valves and can be controlled by using a shock arrestor.

installed with a pressure reducing valve upstream of the unit. and temperature ranges of  $33^{\circ}$ F (0.5°C) to  $180^{\circ}$ F (82°C). Systems which exceed 60psi shall be Series SA-1 is designed for new or existing water lines with pressures up to 150psi (10.3 bar)

possible. Allow sufficient clearance for installation. Select a location as close to the source of shock (i.e. dishwasher, icemaker, toilet or faucet) as

shock would be absorbed most effectively. Although they function in any orientation, Figure 1 and 2 show the proper installation where the For your safety these units are pre-charged at the factory and are not rechargeable or repairable.

# Shock Source - - - . 'BZ.'G · - - - -Shock Source Figure 2 Figure 1



# **WARNING:** This product contains chemicals CALIFORNIA PROPOSITION 65 WARNING

to customers in the State of California.) (California law requires this warning to be given and birth defects or other reproductive harm. known to the State of California to cause cancer

#### For more information: www.watts.com/prop65

Company will, at its option, replace or recondition the product without charge. for a period of one year from the date of original shipment. In the event of such defects within the warranty period, the Limited Warranty: FEBCO warrants each product to be free from defects in material and workmanship under normal usage

LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. COMPANY HEREBY SPECIFICALLY DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT WITH RESPECT TO THE PRODUCT. THE COMPANY MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED. THE THE WARRANTY SET FORTH HEREIN IS GIVEN EXPRESSLY AND IS THE ONLY WARRANTY GIVEN BY THE COMPANY

This warranty shall be invalidated by any abuse, misuse, misapplication, improper installation or improper maintenance or damage from adverse water conditions, chemical, or any other circumstances over which the Company has no control. work properly, other costs resulting from labor charges, delays, vandalism, negligence, fouling caused by foreign material, without limitation, lost profits or the cost of repairing or replacing other property which is damaged if this product does not of warranty, and the Company shall not be responsible for any incidental, special or consequential damages, including The remedy described in the first paragraph of this warranty shall constitute the sole and exclusive remedy for breach

FITNESS FOR A PARTICULAR PURPOSE, ARE LIMITED IN DURATION TO ONE YEAR FROM THE DATE OF ORIGINAL WARRANTIES THAT MAY NOT BE DISCLAIMED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND applicable state laws to determine your rights. SO FAR AS IS CONSISTENT WITH APPLICABLE STATE LAW, ANY IMPLIED Warranty gives you specific legal rights, and you may have other rights that vary from State to State. You should consult or limitation of incidental or consequential damages. Therefore the above limitations may not apply to you. This Limited Some States do not allow limitations on how long an implied warranty lasts, and some States do not allow the exclusion alteration of the product.

#### CERTIFIED 120 9001-2000

USA: 4381 N. Brawley • Ste. 102 • Fresno, CA • 93722

 Tel. (905) 332-4090 • Fax: (905) 332-7068 • www.FEBC0online.ca Canada: 5435 North Service Rd. • Burlington, OVT. • L7L 5H7 • Tel. (559) 441-5300 • Fax: (559) 441-5301 • www.FEBCOonline.com

A Division of Watts Water Technologies, Inc.

© FEBCO, 2008 EDb# 1012060 3480 I-A2-7-SI