



C-MAX®

Full product line of extruded carbon block cartridges for a wide range of water quality improvement applications

C-MAX[®] Extruded Carbon Filter Cartridges

Full line of solid block activated carbon cartridges for water treatment.



Standard cartridges

Full-Flow(B-B)

Full product line with color coded end caps to indicate cartridge type




Cartridge selection guide

Cartridge type	Wall	Carbon Type	Micron	Particle Size	Very High Sediment Removal	Very High Chlorine Reduction	Cysts	VOCs	Lead
MAX-ETW	Thick	Bituminous	5	Medium					
MAX-S	Thick	Coconut shell	5	Medium	•				
MAX-CYST	Thick	Bituminous	0.5	Fine			٠		
MAX-VOC	Thick	Coconut shell	0.5	Fine			•	•	
MAX-T	Thick	Coconut shell	5	Medium					
MAX-PB	Thick	Coconut shell	0.5	Fine			٠		•
MAX-CL	Thick	Bituminous	0.5	Fine		•			



C-MAX[®] carbon block cartridges are tested and certified by NSF International under NSF / ANSI Standard 42 for materials only. Performance claims are supported by company test results.

Note: C-MAX cartridges are rated for temperatures to 165°F (74°C).




Low Pressure Drop

The chart above compares the pressure drop of MAXETW cartridges to another well known brand. This data demonstrates flow restrictions are dramatically reduced using MAXETW cartridges and not all carbon block cartridges perform the same.



C-MAX®

Your best choice when both price and performance are required!



High Chlorine Reduction

Chlorine reduction with MAXETW carbon block cartridges is dramatically greater than other cartridge types, including granular activated carbon cartridges. The above data is typical for GAC and C-MAX cartridges during their usable life.

MAX-ETW, Economical, thick wall carbon block cartridges for Chlorine taste and odor

Part Number	Туре	OD	Length	Micron Rating	Chlorine Reduction	No. / Case
MAXETW-975	Thick Wall	2-7/8"	9-3/4"	5 nominal	3,000 gallons	12
MAXETW-20	Thick Wall	2-7/8"	20"	5 nominal	6,000 gallons	6
MAXETW-30	Thick Wall	2-7/8"	30"	5 nominal	9,000 gallons	6
MAXETW-40	Thick Wall	2-7/8"	40"	5 nominal	12,000 gallons	6
MAXETW-FF975	Thick Wall	4-5/8"	9-3/4"	5 nominal	11,000 gallons	4
MAXETW-FF20	Thick Wall	4-5/8"	20"	5 nominal	20,000 gallons	6

MAX-S, Thick wall coconut shell carbon block cartridges for high dirt holding capacity

Part Number	Туре	OD	Length	Micron Rating	Chlorine Reduction	No. / Case
MAXS-975	Thick Wall	2-7/8"	9-3/4"	5 nominal	6,000 gallons	12
MAXS-20	Thick Wall	2-7/8"	20"	5 nominal	12,000 gallons	6
MAXS-FF975	Thick Wall	4-5/8"	9-3/4"	5 nominal	22,000 gallons	4
MAXS-FF20	Thick Wall	4-5/8"	20"	5 nominal	40,000 gallons	6

MAX-CYST, Thick wall carbon block cartridges for fine particles, cyst reduction & extended Chlorine taste & odor reduction

Part Number	Туре	OD	Length	Micron Rating	Chlorine Reduction	No. / Case
MAXCYST-975	Long life + cysts	2-7/8"	9-3/4"	0.5 nominal	20,000 gallons	12
MAXCYST-20	Long life + cysts	2-7/8"	20"	0.5 nominal	45,000 gallons	6
MAXCYST-FF975	Long life + cysts	4-5/8"	9-3/4"	0.5 nominal	50,000 gallons	4
MAXCYST-FF20	Long life + cysts	4-5/8"	20"	0.5 nominal	150,000 gallons	6

Full line of solid block activated carbon cartridges for water treatment.

MAX-VOC, Coconut shell carbon block cartridges for reduction of VOC's, cysts and extended Chlorine taste and odor reduction

Part Number	Туре	OD	Length	Micron Rating	Chlorine Reduction	No. / Case
MAXVOC-975	Water washed	2-7/8"	9-3/4"	0.5 nominal	20,000 gallons	12
MAXVOC-20	Water washed	2-7/8"	20"	0.5 nominal	40,000 gallons	6
MAXVOC-FF975	Water washed	4-5/8"	9-3/4"	0.5 nominal	50,000 gallons	4
MAXVOC-FF20	Water washed	4-5/8"	20"	0.5 nominal	150,000 gallons	6

MAX-T, Acid washed coconut shell carbon block cartridges for RO post treatment and improved, sweeter taste

Part Number	Туре	OD	Length	Micron Rating	Chlorine Reduction	No. / Case
MAXT-975	Acid washed	2-7/8"	9-3/4"	5 nominal	5,000 gallons	12
MAXT-20	Acid washed	2-7/8"	20"	5 nominal	10,000 gallons	6
MAXT-FF975	Acid washed	4-5/8"	9-3/4"	5 nominal	18,000 gallons	4
MAXT-FF20	Acid washed	4-5/8"	20"	5 nominal	32,000 gallons	6

MAX-PB, Coconut shell carbon block cartridges for Lead and cyst reduction

Part Number	Туре	OD	Length	Micron Rating	Chlorine Reduction	No. / Case
MAXPB-975	Lead + cysts	2-7/8"	9-3/4"	0.5 nominal	20,000 gallons	12
MAXPB-20	Lead + cysts	2-7/8"	20"	0.5 nominal	40,000 gallons	6
MAXPB-FF975	Lead + cysts	4-5/8"	9-3/4"	0.5 nominal	50,000 gallons	4
MAXPB-FF20	Lead + cysts	4-5/8"	20"	0.5 nominal	150,000 gallons	6

MAX-CL, Thick wall carbon block for long life and high chlorine reduction. Reduces tastes, odors, fine particles. The best choice when a "super chlorine guzzler" is needed!

Part Number	Туре	OD	Length	Micron Rating	Chlorine Reduction	No. / Case
MAXCL-975	Thick Wall	2-7/8"	9-3/4"	0.5 nominal	20,000 gallons	12
MAXCL-20	Thick Wall	2-7/8"	20"	0.5 nominal	45,000 gallons	6
MAXCL-FF975	Thick Wall	4-5/8"	9-3/4"	0.5 nominal	70,000 gallons	4
MAXCL-FF20	Thick Wall	4-5/8"	20"	0.5 nominal	150,000 gallons	6

Distributed by:		

Printed in USA