
Controls and Accessories

LEAD FREE*

Model LF60-1 Y-Pattern Strainer Size: ¹/₄" - ³/₄" NPT

Model LF60-1 Y-Pattern Strainers are used to filter the fluid passing through the pilot circuit, and provide protection to pilot circuit speed controls and pilots. The filter element can be accessed for cleaning by removing the clean-out cap, or may be cleaned by installing an optional "blow-down" ball valve.





Dimensions

SIZE	DIMENSIONS				WEIGHT	
	A		В			
in.	in	mm	in	mm	lbs.	kgs.
1⁄4	211/16	68	111/16	43	1.7	0.77
3/8	211/16	68	111/16	43	1.7	0.77
1/2	3	76	2	51	1.7	0.77
3⁄4	35/16	84	25/16	59	1.7	0.77

Specifications

Body Material:	Lead Free Copper Silicon Alloy CF8M (316) Stainless Steel (optional)			
Retainer Cap:	Lead Free Copper Silicon Alloy			
Cap Gasket:	EPDM			
Pressure Rating:	400psi (27.6 bar)			
Filter Element:	304 Stainless Steel			
Mesh Options:	60 Mesh (standard) 100 Mesh (optional)			

*The wetted surface of this product contacted by consumable water contains less than 0.25% of lead by weight.

NOTICE

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.

Ames Fire & Waterworks product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Ames Fire & Waterworks Technical Service. Ames Fire & Waterworks reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Ames Fire & Waterworks products previously or subsequently sold.



A Watts Water Technologies Company

USA: Tel: (713) 943-0688 • Fax: (713) 944-9445 • Watts.com **Canada:** Tel: (905) 332-4090 • Fax: (905) 332-7068 • Watts.ca **Latin America:** Tel: (52) 81-1001-8600 • Fax: (52) 81-8000-7091 • Watts.com