## Models: 185SS, 186SS

Job Name	Contractor
Job Location	Approval
Engineer	Contractor's P.O. No
Approval	Representative



# Cast Stainless Steel Flanged End Basket Strainers

Model: 185SS, 186SS

Sizes: 11/2" - 20"

PRESSURE/TEMPERATURE-NON-SHOCK								
MODEL	MATERIAL	RATING						
185-SS		275psi @ -20°F to 100°F						
	Stainless Steel	18.96 bar @ 37.78°C						
		150psi @ 565°F						
		10.34 bar @ 296.11°C						
186-SS		720psi @ -20°F to 100°F						
	Stainless Steel	49.64 bar @ 37.78°C						
		395psi @ 850°F						
		27.23 bar @ 454.44°C						

\*Max. temp. can be limited by gasket material. Consult factory.

185-SS	Class 150
186-SS	Class 300

## **Typical Service**

- These rugged strainers can be specified for many applications in chemical processes, including brine, paint, fuel oil, organic and inorganic chemicals, as well as condensers and heat exchangers, to name just a few.
- They are especially suited for medium or coarse straining. For finer straining, see Model 125F-SS or 126F-SS.

## Features

- The angular cutaway design of the baskets allows a straight through flow, resulting in extremely low pressure drop.
- Tapped and plugged NPT drain on the strainer bottom enables easy self-cleaning on open bottom baskets. Simply open the valve or plug on the outlet to flush accumulated particles.
- Bodies can be tapped for pressure gauges, or per customer requirement, consult factory.

## Construction

• Cover is a flanged bolted design for easy basket removal.



Models 185-SS, 186-SS

#### Capacity

• Large bodies and generous sized baskets

• Minimum 6 to 1 ratio.

## **Special Coatings and Treatments**

• Pickling and passivation are available, consult factory.

#### Steam Jacketing

Available on request, consult factory.

#### **Baskets**

			IDARD Ater)		AM NDATION	
MODEL	SIZES	MATERIAL	OPENING	MATERIAL	OPENING	
185-SS/186-SS	11⁄2" - 4"	304SS	.062 perf	304SS	.045 perf	
185-SS/186-SS	5" and Up	304SS	.125 perf	Consult Factory		

#### NOTICE

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.

\*The wetted surface of this product contacted by consumable water contains less than 0.25% of lead by weight.

Mueller Steam Specialty product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Mueller Steam Specialty Technical Service. Mueller Steam Specialty reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Mueller Steam Specialty products previously or subsequently sold.



A WATTS Brand

#### Material

BILL OF MATERIAL MODELS 185SS, 186SS								
ITEM	DESCRIPTION MATERIAL							
1	BODY	BODY Stainless Steel ASTM A351 Grade CF8M						
2	COVER** Stainless Steel ASTM A351 Grade CF8M							
3	COVER GASKET	316 Filled Graphoil						
4	BASKET	BASKET 304 SS						
5	5 STUDS ASTM A193 B8M							
6	NUTS	ASTM A194 8M						
7	PLUG	ASTM A351 CF8M						
** Cover may be manufactured from equivalent grade plate material								

## **Pressure Drop**

See Pressure Drop Charts in Technical Data section of the Mueller Steam Specialty Engineering binder. Cv values are noted in the Dimensions and Weights table below.

## **Dimensions and Weights**

SIZE	DIMENSIONS										WEI	GHT	CV
	A	4		В	C D		)	E					
							(NPT)		Screen				
									Rem				
in.	in.	тт	in.	mm	in.	тт	in.	тт	in.	тт	lbs.	kgs.	GPM
	185SS												
1½	6½	165	<b>4</b> <sup>1</sup> / <sub>8</sub>	105	4	102	1/2	15	10"	254	23	10.4	43
2	81/2	216	57/8	149	43/4	121	1/2	15	121/2"	318	34	15.4	45
<b>2</b> <sup>1</sup> / <sub>2</sub>	8	203	51/16	138	<b>4</b> <sup>1</sup> / <sub>4</sub>	108	3⁄4	20	12½"	318	34	15.4	85
3	83⁄4	222	51⁄4	133	5½	140	3⁄4	20	12½"	318	46	20	140
4	<b>11</b> <sup>3</sup> ⁄16	284	71/8	200	6	152	1	25	16½"	419	70	31	290
5	121/4	311	10¼	260	5%	143	1	25	16½"	419	108	49	500
6	131/8	352	121/2	318	5 <sup>13</sup> /16	148	11/4	32	19"	483	168	76	800
8	17%	441	151%	384	8	203	1½	40	26"	660	234	106	1,600
10	22	549	16	406	10%	264	1½	40	301/2"	775	402	182	3,200
12	25	635	23¾	603	12%	314	2	50	-	-	692	314	5,000
14	471/8	1197	34%	873	<b>20</b> <sup>3</sup> ⁄16	513	2	50	68¼"	1734	CF	CF	7,500
16	471/8	1197	34%	873	<b>20</b> ¾16	513	2	50	68¼"	1734	CF	CF	9,500
18	34	864	36	914	16¼	413	2	50	56"	1422	CF	CF	13,500
20	36¾	934	401%	1038	17	432	2	50	61"	1549	CF	CF	17,500
186SS	5												
11/2	7	178	<b>4</b> <sup>1</sup> / <sub>8</sub>	105	4	102	1/2	15	10"	254	23.3	11.6	43
2	81/2	216	51%	149	43/4	121	1/2	15	12½"	318	34.3	15.5	45
21/2	811/16	221	<b>5</b> 7⁄16	138	41/4	108	3⁄4	20	121/2"	318	39.8	17	85
3	<b>9</b> %16	243	51/4	133	51/2	140	3⁄4	20	12½"	318	54	24	140
4	11¾	298	71/8	200	6	152	1	25	16½"	419	86	39	290
5	131/8	333	101/4	260	55/8	143	1	25	161⁄2"	419	121	55	500
6	143⁄4	375	12½	318	5 <sup>13</sup> /16	148	11/4	32	19"	483	196	89	800
8	181/8	460	151/8	384	8	203	1½	40	26"	660	292	132	1,600
10	227/8	581	16	406	10%	264	1½	40	301/2"	775	460	209	3,200
12	253/8	645	23¾	603	12%	314	2	50	-	-	790	359	5,000
14	471/8	1197	34%	873	<b>20</b> <sup>3</sup> ⁄16	513	2	50	68¼"	1734	CF	CF	7,500
16	471/8	1197	34%	873	<b>20</b> <sup>3</sup> /16	513	2	50	681/4"	1734	CF	CF	9,500
18	35%	905	36	914	161/4	413	2	50	56"	1422	CF	CF	13,500
20	383/8	975	401%	1038	17	432	2	50	61"	1549	CF	CF	17,500

Apply For Certified Drawings. Larger sizes available.


CF=Consult Factory

Limited Warranty: Mueller Steam Specialty warrants each product to be free from defects in material and workmanship under normal usage for a period of one year from the date of original shipment. In the event of such defects within the warranty period, the Company will, at its option, replace or recondition the product without charge. This shall constitute the sole and exclusive remedy for breach of warranty, and the Company shall not be responsible for any incidental, special or consequential damages, including without limitation, lost profits or the cost of repairing or replacing other property which is damaged if this product does not work properly, other costs resulting from labor charges, delays, vandalism, negligence, fouling caused by foreign material, damage form adverse water conditions, chemical, or any other circumstances over which the Company has no control. This warranty shall be invalidated by any abuse, misuse, misapplication or improper installation of the product. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Any implied warranties that are imposed by law are limited in duration to one year.

Some States do not allow limitations on how long an implied warranty lasts, and some States do not allow the exclusion or limitation of incidental or consequential damages. Therefore the above limitations may not apply to you. This Limited Warranty gives you specific legal rights, and you may have other rights that vary from State to State. You should consult applicable state laws to determine your rights.



A WATTS Brand



Models 185-SS, 186-SS