Models: 781*, 781-WE*

Job Name	Contractor
Job Location	Approval
	7.pprovar
Engineer	Contractor's P.O. No.
Approval	Representative

LEAD FREE*

Cast Carbon & Alloy Steel Flanged & Butt Weld End Y Strainers

Models: 781*, 781-WE

Sizes: 1/2" - 24"

PRESSURE/TEMPERATURE-NON-SHOCK									
MODEL	MATERIAL	RATING							
		285 psi @ -20 to 100°F							
781, 781-WE	Carbon Steel	19.6 bar @ 38°C							
701, 701-WE	Gaibon Steel	150psi @ 565°F							
		10.2 bar @ 300°C							
		290psi @ -20 to 100°F							
701 701 WE	Chromo Mohr	19.8 bar @ 38°C							
781, 781-WE	Chrome Moly	150psi @ 565°F							
		10.2 bar @ 300°C							

781 Class 150 781-WE Class 150

Features

- Machined seats in both body and cap align and lock the screen in place to stop sediment bypass.
- Machined seats facilitate alignment and accurate reseating after servicing.

Construction

- Designed for Class 150 specifications.
- Heavy gauge reinforced screens are used.

IMPORTANT NOTE: Model 781-WE ends are machined to match Schedule 40 pipe. Other connections are available, consult factory.

Self-Cleaning

• Self-cleaning is accomplished by opening the plug or valve connected to the blowoff outlet.

Blowoff Outlets

- Blowoff outlets are NPT tapped at location C. See next page for NPT sizes.
- Blind covers are available, consult factory.



Model 781



Model 781-WE

* 781/781-WE supersedes model 761/741-WE. 761/761-WE available upon request.

Capacity

- Generously proportioned bodies.
- Open Area Ratio much greater than pipe size, ensuring low pressure drop.

Screens

		STANDARI	D (WATER)	STEAM RECOMENDATION			
MODEL	SIZES	MATERIAL	OPENING	MATERIAL	OPENING		
1/2" - 4"	All	304SS	.062 perf	304SS	.045 perf		
5" and Un	All	304SS	125 nerf	304SS	.062 perf		

NOTICE

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.

*The wetted surface of this product contacted by consumable water contains less than 0.25% of lead by weight.

Mueller Steam Specialty product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Mueller Steam Specialty Technical Service. Mueller Steam Specialty reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Mueller Steam Specialty products previously or subsequently sold.



BILL OF MATERIAL MODELS 781, 781-WE										
ITEM	DESCRIPTION	MATERIAL								
1	BODY	Carbon Steel ASTM A216 Grade WCB								
2	COVER **	Carbon Steel ASTM A216 Grade WCB								
3	SCREEN	304 SS								
4	GASKET	Compressed Non-Asbestos								
5	STUDS	A193 B7								
6	NUTS	A194 2H								

^{**} Cover may be manufactured from equivalent grade plate material

Also Available:

Body/Cap: Carbon-Moly ASTM A217 Gr. WC1 Chrome-Moly ASTM A217 Gr. WC6 Chrome-Moly ASTM A217 Gr. WC9

Pressure Drop


See Pressure Drop Charts in Technical Data section of the Mueller Steam Specialty Engineering binder. Cv values are noted in the Dimensions and Weights table below.

Dimensions and Weights


SI	ZE	DIMENSIONS							WEI	Cv		
		1	A		3	C (1	NPT)	D Screen Removal				
in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	lbs.	kgs.	GPM
1/2	15	57/8	149	31/2	89	3/8	10	5	130	5.5	2.5	8
3/4	20	7%	187	33/4	95	1/2	15	5	130	10.25	4.6	15
1	25	7%	187	3¾	95	1/2	15	5	130	10.25	4.6	22
11/4	32	7	178	43/4	121	1/2	15	7	178	9.75	4.4	38
11/2	40	71//8	181	43/4	121	1/2	15	7	178	12.5	5.6	42
2	50	71//8	200	51/4	133	1/2	15	7	178	18	8.1	70
21/2	65	93/4	248	61/2	165	1	25	93/4	248	28	12.7	110
3	80	101/16	256	7	178	1	25	10	254	34	15	140
4	100	121//8	308	81/4	210	11/2	40	12	305	55	25	245
5	125	15%	397	111/4	286	2	50	20	508	90	40	400
6	150	181/2	470	131/2	343	2	50	20	508	153	69	600
8	200	21%	543	15½	394	2	50	223/4	578	220	100	1,000
10	250	26	660	181/2	470	2	50	28	711	320	145	1,580
12	300	297/8	759	221/4	565	2	50	30	762	550	250	2,200
14	350	36	914	25	635	2	50	36½	927	975	442	3,200
16	400	41%16	1056	26½	673	2	50	42	1067	1635	741	4,900
18	450	46	1168	341//8	886	2	50	50%	1292	2376	1078	6,100
20	500	491/2	1257	39	991	2	50	55%	1407	2675	1213	8,000
24	600	58%	1483	441/6	1122	2	50	671/4	1708	4880	2213	11,000

In.	VILL			Dime	1010110				WEIGHT		•		
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$			1	A		В	C (NIDT)		-				
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	lbs.	kgs.	GPM
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	1/2	15	6%	168	31/2	89	3/8	10	5	130	3	1.3	8
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	3/4		85/16	211	33/4			15	5	130	9	4	15
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	1												
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$			101//8						/				
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	11/2		101/4	279	51/4				7	178	13		
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$			101/4	219	51/4	133	1/2			178	10		70
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$							1						
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	3			305	'		1						
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	4		141/2	368						305			245
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	5		195/16							508			400
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	6	150	195/16	491		343	2	50	20	508	90	40	600
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	8	200	23%	594	15¾	400	2	50	223/4	578	168	76	1,000
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	10	250	27%	695	19	483	2	50	28	711	250	113	1,580
16 400 41½ 1056 26½ 673 2 50 42 1067 1433 650 4,900 18 450 46 1168 34½ 886 2 50 50½ 1292 2152 976 6,100 20 500 49½ 1257 39 991 2 50 55½ 1407 2393 1085 8,000	12	300	32	813	221/2	565	2	50	30	762	440	200	2,200
18 450 46 1168 34% 886 2 50 50% 1292 2152 976 6,100 20 500 49½ 1257 39 991 2 50 55% 1407 2393 1085 8,000	14	350	36	914	25	635	2	50	361/2	927	815	370	3,200
20 500 49½ 1257 39 991 2 50 55% 1407 2393 1085 8,000	16	400	411/6	1056	261/2	673	2	50	42	1067	1433	650	4,900
	18	450	46	1168	347/8	886	2	50	507/8	1292	2152	976	6,100
24 600 58% 1483 44% 1122 2 50 67¼ 1708 4486 2034 11,000	20	500	491/2	1257	39	991	2	50	55%	1407	2393	1085	8,000
	24	600	58%	1483	441/6	1122	2	50	671/4	1708	4486	2034	11,000

Materials



Model 781



Model 781-WE

Apply for certified drawing

Limited Warranty: Mueller Steam Specialty warrants each product to be free from defects in material and workmanship under normal usage for a period of one year from the date of original shipment. In the event of such defects within the warranty period, the Company will, at its option, replace or recondition the product without charge. This shall constitute the sole and exclusive remedy for breach of warranty, and the Company shall not be responsible for any incidental, special or consequential damages, including without limitation, lost profits or the cost of repairing or replacing o

Some States do not allow limitations on how long an implied warranty lasts, and some States do not allow the exclusion or limitation of incidental or consequential damages. Therefore the above limitations may not apply to you. This Limited Warranty gives you specific legal rights, and you may have other rights that vary from State to State. You should consult applicable state laws to determine your rights.

