WATTS DRAINAGE	FD-350 Tag:	Area Drain with 12" Round Top
Components:		B6 FD-340
serrated anchor flange, weepholes, co and no hub (MJ) (standard) outlet.	Allar and 12"(305) round epoxy coated a 1"(25) THICK HEAVY DL EPOXY COATED DUCTI IRON GRATE 3/8"(10) A WiDTH DRAINAG SLOTS BROAD SERRA ANCHOR FLAN LARGE CAST WEEPHOLES "B6" EXTRA DEEP SUMP BODY PUSH-ON SHOW PIPE SIZE "(76), 4"(102) H (MJ) only (P) PUSH-ON GASK (ASTM C-564)	TY Order Code: FD-35 - FX FD-352P-1 Viffix Description 2 2°(51) Pipe Size 3 3°(76) Pipe Size 4 4°(102) Pipe Size 6 6°(152) Pipe Size 6 6°(152) Pipe Size NAX Dutlet Type (Select One) Suffix Description NH No Hub (MI) P Push On T Threaded Outlet X Inside Caulk NH Nickel Bronze 4 Ductile Iron Options (Select One or More) Suffix Description 1 Nickel Bronze 4 Ductile Iron NN -5 Sediment Bucket -6 Vandal Proof -8 Backwater Valve (3" 4" Only) 10 Secured Top -13 All Galvanized -15 Extension (4") -13 All Galvanized -15 Extension (4") -13 All Galvanized -15
Job Name Contractor		
Job Location		D
Engineer Representative		
WATTS Drainage reserves the right to modify or change product design or construction without prior notice and without incurring any obligation to make similar changes and modifications to products previously or subsequently sold. See your WATTS Drainage representative for any clarification. Dimensions are subject to manufacturing tolerances.		

ES-WD-FD-350 CANADA 0403