WATTS DRAINAGE	RD-100-W Tag:	Large Area Roof Drain with Internal Standpipe
Components:	B2 B2-W B	
device with integral gravel stop and s	serrated flashing flange, flashing clam elf-locking polyethylene dome strainer. 860) 8"(203) HIGH SELF-LOCKIN POLYETHYLEN DOME 4"(102) DIAMETER STANDPIPE 4"(102) OR AS SPECIFIED 4"(102) OR AS SPECIFIED FLASHING CLAMP & GRAVEL ST 2-5/16"(59) WIDE SERRATED CLAMPIN SURFACE "B2" BODY PUSH-ON GASKET (ASTM C-564)	Ex. RD-102P-W-K Pipe Sizing (Select One) Suffix Description 2 2"(51) Pipe Size 3 3"(76) Pipe Size 4 4"(102) Pipe Size 5 5"(127) Pipe Size 6 6"(152) Pipe Size 8 8"(203) Pipe Size Outlet Type (Select One) Suffix Description NH No Hub (MJ) P Push On T Threaded Outlet X Inside Caulk Dyteoma Receiver Plange BED Sump Receiver Flange BED Sump Receiver Adj Ext., Deck Clamp D C Secondary Membrane Clamp D Underdeck Clamp BED Stainless Steel Ballast Guard H Adj. to 6" IRMA Ballast Guard H Adj. to 6" IRMA Ballast Guard H Adj. to 6" IRMA Ballast Guard </th
	tions) are not available when -SO is selecte Contractor	
	Contractor's P.O. N	
Engineer Representative		

ES-WD-RD-100-W CANADA 0403