



SG Series
Tag: _____

Copper Shock Arrestors

SPECIFICATION: Watts Drainage SG Series pre-charged hard drawn copper shock arrestor with brass piston, EPDM o-ring seals, and male IPS threaded connection.

OPERATING PRESSURE: Designed to operate on all domestic and commercial lines up to 150psi working pressure.

TEMPERATURE RANGE: 33°F to 180°F (0.5°C to 82°C)



Pipe Sizing (Select One)		
Suffix	Description	
050	1/2"(13) Connection	<input type="checkbox"/>
075	3/4"(19) Connection	<input type="checkbox"/>
100	1"(25) Connection	<input type="checkbox"/>
125	1"(25) Connection	<input type="checkbox"/>
150	1"(25) Connection	<input type="checkbox"/>
200	1"(25) Connection	<input type="checkbox"/>

	TECHNICAL DATA					
	SG-050	SG-075	SG-100	SG-125	SG-150	SG-200
Fixture Unit	1-11	12-32	33-60	61-113	114-154	155-330
Connection	1/2" (13)	3/4"(25)	1"(25)	1" (25)	1" (25)	1" (25)
"A" Diameter	1-1/8"(29)	1-3/8"(35)	1-5/8"(41)	2-1/8"(54)	2-1/8"(54)	2-5/8"(67)
"B" Height	5-5/15"(151)	8-9/16"(217)	8-13/16"(224)	9-15/16"(252)	12-11/16"(322)	11-5/32"(283)

Job Name _____ Contractor _____

Job Location _____ Contractor's P.O. No. _____

Engineer _____ Representative _____

WATTS Drainage reserves the right to modify or change product design or construction without prior notice and without incurring any obligation to make similar changes and modifications to products previously or subsequently sold. See your WATTS Drainage representative for any clarification. Dimensions are subject to manufacturing tolerances.



Specification Drainage Products

USA: 100 Watts Road, Spindale, NC, 28160-2298; TEL: 828-288-2179 TOLL-FREE: 1-800-338-2581 www.watts.com

CANADA: 5435 North Service Rd., Burlington, ON, L7L 5H7 TEL: 905-332-6718 TOLL-FREE: 1-888-208-8927 www.wattscanada.ca