

Tag: __

SPECIFICATION: Watts Drainage Products TD-910-B 12-5/8"(321) wide extra heavy duty epoxy coated ductile iron trench grating with epoxy coated steel anchor frame.	
FUNCTION: For installation in garages, parking areas, ramps, tunnels, process areas subject to both vehicular and pedestrian traffic.	
24-1/2"(62) 24-1/2"(62) 13/16" (21) MAX. WIDTH SLOTS DUCTILE IRON GRATE RECOMMENDED FOR HEAVY DUTY APPLICATIONS 1-3/4"(45) × 1-3/4"(45) × 1/4"(45)	Order Code: TD-910- I2-5/8"(321) I2-5/8"(321) I-3/4"(45) Ex. TD-910-B2-4-1 Fieces (Select One) Suffix Description B1 B2 Piece B3 3 Piece B2 B3 Specify x: I2"(305) Option (Select One or More) Suffix Description -4-3 Ductile Iron Grate w/ Steinless Steel Veneer & Frame -4-3 Ductile Iron Grate w/ Steinless Steel Veneer & Frame -6 Option (Select One or More) Suffix Description -6 Vandal proof -10 Secured Top -13 Galvanized Grate & Frame
Load Rating & Free AreaLoad RatingFree Area Sq. In.*XHD52/ft*XHD52/ft*Boy Colspan="2">* Colspan="2">* The load classifications are in accordance with the American National Standards ASME A112.21.1M ASME Ratings are as follows: XHD - Safe Live Load 7500-10000 lbs.(3375-4500kg) The above categories are given as a guide only. Please consult factory.	
Job Name	Contractor
Job Location	Contractor's P.O. No.
Engineer	Representative
WATTS Drainage reserves the right to modify or change product design or construction without prior notice and without incurring any obligation to make similar changes and modifications to products previously or subsequently sold. See your WATTS Drainage representative for any clarification. Dimensions are subject to manufacturing tolerances.	
© Watts Drainage 2004	