

For Residential and Commercial Applications

Job Name _____

Contractor _____

Job Location _____

Approval _____

Engineer _____

Contractor's P.O. No. _____

Approval _____

Representative _____

Brass CrimpRing™ Adapters

Brass CrimpRing™ Sweat Adapters are used to transition copper pipe to WaterPEX® supply lines. Threaded Adapters are used for the appropriate NPT fitting.

Specifications

System shall be plumbed using Watts WaterPEX® cross-linked polyethylene pipe. All joints shall be made using Watts brass CrimpRing™ and/or polyalloy CrimpRing™ fittings using either the Watts copper CrimpRing™ or stainless steel CinchClamp™* crimping methods as outlined in the Watts WaterPEX® Installation Guidelines.

Installation Note

CrimpRing™ Adapters must be installed in accordance with all Watts WaterPEX® installation procedures, including information provided in WaterPEX® installation manual and guidelines.

Approvals



- Manufactured in accordance with American Society for Testing and Materials (ASTM) F-877 and F-1807
- Listed by the National Sanitation Foundation to NSF Standards 14 and 61 for use in potable water systems
- Listed by NSF to be in compliant to the Uniform Plumbing Code
- Labeled B137.5 which indicates that it is compliant to the CSA Standards B137.5

* **Note:** Watts WaterPEX CinchClamp™ fittings should not be used with wrought copper PEX fittings.

Warning!

If connections must be made in temperatures below 30°F, caution must be taken to allow the WaterPEX to form a proper seal against the barb. Apply the connection slowly to ensure the PEX material conforms to the barb.




WP10
Male Sweat x Crimp
Adapter



WP11
Female Sweat x Crimp
Adapter



WP13
Crimp x FPT Threaded
Adapter



WP12
Crimp x MPT Threaded
Adapter

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.

WATTS®

Dimensions – Weights

MODEL	INLET			OUTLET			PKG. WEIGHT	
	<i>in.</i>	<i>mm</i>	<i>type</i>	<i>in.</i>	<i>mm</i>	<i>type</i>	<i>lbs.</i>	<i>kgs.</i>
CrimpRing™ Sweat Adapters — Male x Crimp								
WP10B-0806PB	½	15	Male Sweat	⅜	10	Crimp Fitting	1	0.5
WP10B-0808PB	½	15	Male Sweat	½	15	Crimp Fitting	1	0.5
WP10B-1212PB	¾	20	Male Sweat	¾	20	Crimp Fitting	1	0.5
WP10B-1616PB	1	25	Male Sweat	1	25	Crimp Fitting	2	0.9
WP10B-1620PB	1	25	Male Sweat	1¼	32	Crimp Fitting	3	1.4
WP10B-2020PB	1¼	32	Male Sweat	1¼	32	Crimp Fitting	4	1.8
CrimpRing™ Sweat Adapters — Female x Crimp								
WP11B-0808PB	½	15	Female Sweat	½	15	Crimp Fitting	1	0.5
WP11B-1212PB	¾	20	Female Sweat	¾	20	Crimp Fitting	2	0.9
WP11B-1616PB	1	25	Female Sweat	1	25	Crimp Fitting	3	1.4
WP11B-1620PB	1	25	Female Sweat	1¼	32	Crimp Fitting	3	1.4
WP11B-2020PB	1¼	32	Female Sweat	1¼	32	Crimp Fitting	4	1.8
CrimpRing™ Threaded Adapters — Crimp x Male								
WP12B-0608PB	⅜	10	Crimp Fitting	½	15	MPT	1	0.5
WP12B-0808PB	½	15	Crimp Fitting	½	15	MPT	1	0.5
WP12B-0812PB	½	15	Crimp Fitting	¾	20	MPT	2	0.9
WP12B-1208PB	¾	20	Crimp Fitting	½	15	MPT	1	0.5
WP12B-1212PB	¾	20	Crimp Fitting	¾	20	MPT	2	0.9
WP12B-1216PB	¾	20	Crimp Fitting	1	25	MPT	3	1.4
WP12B-1612PB	1	25	Crimp Fitting	¾	20	MPT	3	1.4
WP12B-1616PB	1	25	Crimp Fitting	1	25	MPT	3	1.4
WP12B-2016PB	1¼	32	Crimp Fitting	1	25	MPT	3	1.4
WP12B-2020PB	1¼	32	Crimp Fitting	1¼	32	MPT	2	.9
WP12B-20M20CPB	1¼	32	MPT	1¼	32	Crimp Fitting	4	1.8
CrimpRing™ Threaded Adapters — Crimp x Female								
WP13B-0808PB	½	15	Crimp Fitting	½	15	FPT	1	0.5
WP13B-1212PB	¾	20	Crimp Fitting	¾	20	FPT	2	0.9
WP13B-20F20CPB	1¼	32	FPT	1¼	32	Crimp Fitting	4	1.8



WaterPEX Plumbing Products



USA: 815 Chestnut St., No. Andover, MA 01845-6098; www.watts.com

Canada: 5435 North Service Rd., Burlington, ONT. L7L 5H7; www.wattscanada.ca