

For Residential and Commercial Applications

Job Name _____

Contractor _____

Job Location _____

Approval _____

Engineer _____

Contractor's P.O. No. _____

Approval _____

Representative _____

Brass CrimpRing™ Tees

Brass CrimpRing™ Tees are used for making directional changes in potable systems.

Specifications

System shall be plumbed using Watts WaterPEX® cross-linked polyethylene pipe, and all joints shall be made using Watts brass CrimpRing™ and/or polyalloy CrimpRing™ fittings using either the Watts copper CrimpRing™ or stainless steel CinchClamp™* crimping methods as outlined in the Watts WaterPEX® Installation Guidelines.

Installation Note

CrimpRing™ Tees must be installed in accordance with all Watts WaterPEX® installation procedures, including information provided in WaterPEX® installation manual and guidelines.

Approvals



- Manufactured in accordance with American Society for Testing and Materials (ASTM) F-877 and F-1807
- Listed by the National Sanitation Foundation to NSF Standards 14 and 61 for use in potable water systems
- Listed by NSF to be in compliant to the Uniform Plumbing Code
- Labeled B137.5 which indicates that it is compliant to the CSA Standards B137.5

* **Note:** Watts WaterPEX CinchClamp™ fittings should not be used with wrought copper PEX fittings.

Warning!

If connections must be made in temperatures below 30°F, caution must be taken to allow the WaterPEX to form a proper seal against the barb. Apply the connection slowly to ensure the PEX material conforms to the barb.



WP18
CrimpRing™ Tee

Dimensions – Weights



MODEL	1			2			3			PKG. WEIGHT	
	in.	mm	type	in.	mm	type	in.	mm	type	lbs.	kgs.
WP18B-06PB	3/8	10	Crimp Fitting	3/8	10	Crimp Fitting	3/8	10	Crimp Fitting	1	0.4
WP18B-080806PB	1/2	15	Crimp Fitting	1/2	15	Crimp Fitting	3/8	10	Crimp Fitting	1	0.4
WP18B-080608PB	1/2	15	Crimp Fitting	3/8	10	Crimp Fitting	1/2	15	Crimp Fitting	1	0.4
WP18B-080606PB	1/2	15	Crimp Fitting	3/8	10	Crimp Fitting	3/8	10	Crimp Fitting	1	0.4
WP18B-08PB	1/2	15	Crimp Fitting	1/2	15	Crimp Fitting	1/2	15	Crimp Fitting	1	0.4
WP18B-080812PB	1/2	15	Crimp Fitting	1/2	15	Crimp Fitting	3/4	20	Crimp Fitting	1	0.4
WP18B-120808PB	3/4	20	Crimp Fitting	1/2	15	Crimp Fitting	1/2	15	Crimp Fitting	1	0.4
WP18B-120812PB	3/4	20	Crimp Fitting	1/2	15	Crimp Fitting	3/4	20	Crimp Fitting	2	0.9
WP18B-121206PB	3/4	20	Crimp Fitting	3/4	20	Crimp Fitting	3/8	10	Crimp Fitting	2	0.9
WP18B-121208PB	3/4	20	Crimp Fitting	3/4	20	Crimp Fitting	1/2	15	Crimp Fitting	2	0.9
WP18B-12PB	3/4	20	Crimp Fitting	3/4	20	Crimp Fitting	3/4	20	Crimp Fitting	2	0.9
WP18B-121216PB	3/4	20	Crimp Fitting	3/4	20	Crimp Fitting	1	25	Crimp Fitting	3	1.4
WP18B-161212PB	1	25	Crimp Fitting	3/4	20	Crimp Fitting	3/4	20	Crimp Fitting	3	1.4
WP18B-161608PB	1	25	Crimp Fitting	1	25	Crimp Fitting	1/2	15	Crimp Fitting	3	1.4
WP18B-161612PB	1	25	Crimp Fitting	1	25	Crimp Fitting	3/4	20	Crimp Fitting	3	1.4
WP18B-16PB	1	25	Crimp Fitting	1	25	Crimp Fitting	1	25	Crimp Fitting	3	1.4
WP18B-202016PB	1 1/4	32	Crimp Fitting	1 1/4	32	Crimp Fitting	1	25	Crimp Fitting	4	1.8
WP18B-20PB	1 1/4	32	Crimp Fitting	1 1/4	32	Crimp Fitting	1 1/4	32	Crimp Fitting	4	1.8

WATTS®

WaterPEX Plumbing Products



**ISO 9001-2000
CERTIFIED**