

## For Residential and Light Commercial Applications

Job Name \_\_\_\_\_

Contractor \_\_\_\_\_

Job Location \_\_\_\_\_

Approval \_\_\_\_\_

Engineer \_\_\_\_\_

Contractor's P.O. No. \_\_\_\_\_

Approval \_\_\_\_\_

Representative \_\_\_\_\_

# LEAD FREE\*

# PURE WATER

## Model PWDWLCV2 Under Counter Water Filtration System

The 2-Stage LCV drinking water system produces high-quality, fresh water on demand by reducing unwanted tastes and odors from your incoming water supply. This system was designed for the Home, RV and Marine Industry where space is at a premium and quality water is essential.

### Features

- 2-Stages of Filtration
  - Stage-1: Sediment filter removes particulates down to 5 micron
  - Stage-2: 1-Micron Carbon Block Filter reduces lead, cysts and VOCs (Cysts include: cryptosporidium, toxoplasma, giardia, and entamoeba)
- Adapt-A-Valve™ for easy installation
- Elegant Chrome long reach faucet included

### Versatility

- Space saving design installs under sink or in limited spaces
- Adapt-A-Valve™ easily connects to water source
- Works in low-pressure applications
- Installs in minutes

### Reliability

- Advanced design uses unique technology and high-quality components to ensure years of continuous trouble-free operation.
- As with all products in the Watts family, the LCV is backed by our reputation of excellence.



PWDWLCV2

### Performance and Benefits

- Reduces chlorine taste and odors, lead, cysts, and VOCs (Cysts include: cryptosporidium, toxoplasma, giardia, and entamoeba)
- Ideal for home, RVs and boats
- Includes dedicated faucet and can be connected to any cold water line
- System goes well beyond basic water filtration and typical "pitcher" or "end-of-tap" filter



System tested and certified by  
WQA against NSF/ANSI Standard  
372 for "lead free" compliance

**Note:** Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected waters that may contain filterable cysts.

\*The wetted surface of this product contacted by consumable water contains less than 0.25% of lead by weight.

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.

## System Specifications

Operating Temperatures: Minimum 40°F (4.4°C),  
Maximum 100°F (37.8°C)

Operating Pressure: Minimum 20psi (1.40 kg/cm<sup>2</sup>),  
Maximum 100psi (7.03 kg/cm<sup>2</sup>)

pH Parameters: Minimum 5, Maximum 10

Flow Rate: 0.5 gpm @ 60 psig

Unit Dimensions: Approx. 11" W x 14.5" H x 5.5" D

Weight: 5 lbs.

## Performance

CERTIFIED FOR	% OF REDUCTION
Cysts	99.95
Cryptosporidium	99.95
Entamoeba	99.95
Giardia	99.95
Toxoplasma	99.95
VOC's	95.00
Lead	96.00
Chlorine	98.00

## Replacement Filters Packs

MODEL	FREQUENCY	DESCRIPTION
PWMB10M5	6 Months	5-micron sediment filter
PWCB10LCV	6 Months	1-micron carbon block filter

**Note:** Water conditions may require more frequent cartridge replacement

*For more information please contact your authorized Watts representative.*



A Watts Water Technologies Company



**USA:** Tel. (800) 224-1299 • [www.watts.com](http://www.watts.com)  
**Canada:** Tel. (888) 208-8927 • [www.watts.ca](http://www.watts.ca)