

All-in-One Ball Valve and Relief Valve

NEW!
Design and
Options

More Functionality, Greater Value

Series LFBRVM1 combines Ball Valve and Relief Valve functions in one easy-to-install valve. It is designed to be used as a water heater shutoff valve and protect against excess water pressure caused by thermal expansion.

Its Lead Free* construction complies with Lead Free* installation requirements. Key features include:

- More end connections — nine different options, using solder, thread, PEX, compression, and barb
- Tighter release pressure tolerances for greater accuracy and safety
- Installs in any position
- Compliance with new IAPMO standard
- CSA approved
- Robust forged body construction
- Industry standard white handle for easy Lead Free* identification
- Competitive pricing for superior value
- Low profile design
- Full port ball valve with virgin PTFE seats
- Blowout proof stem



*The wetted surface of this product contacted by consumable water contains less than 0.25% of lead by weight.

Models

INLET	OUTLET	RELIEF OUTLET	RELIEF PRESSURE
Sweat	Sweat	PEX	80
Sweat	Sweat	Compression	125
Sweat	Sweat	Barb	125
Thread	Thread	Compression	80 or 125
Thread	Thread	Barb	125
PEX	PEX	Compression	125
PEX	PEX	PEX	125
PEX	PEX	Barb	125

Watts.com

WATTS®

USA: T: (978) 689-6066 • F: (978) 975-8350 • Watts.com

Canada: T: (905) 332-4090 • F: (905) 332-7068 • Watts.ca

Latin America: T: (52) 81-1001-8600 • F: (52) 81-8000-7091 • Watts.com

PF-LFBRV 1706

© 2017 Watts