

N170-M2 to M3 Cross Reference Guide



| M2 | | | | M3 | | |
|---------|---------------------|-------------|---|---------|----------------|-------------|
| EDP | Model | Temp. Range | | EDP | Model | Temp. Range |
| 0274193 | 3/4" N 170 M2 | 130 - 180°F | | 0478020 | 3/4" N170-M3 | 90 - 180°F |
| 0274300 | 3/4" N 170L-M2 | 100 - 130°F | ⇒ | | | |
| 0478000 | 3/4" N 170M2-HT | 130 - 180°F | | | | |
| 0274320 | 3/4" N 170L M2-HT | 100 - 130°F | | | | |
| 0274303 | 1" N 170-M2 | 130 - 180°F | | 0478026 | 1" N170-M3 | 90 - 180°F |
| 0274304 | 1" N 170L-M2 | 100 - 130°F | ⇒ | | | |
| 0478001 | 1" N 170M2-HT | 130 - 180°F | | | | |
| 0274321 | 1" N 170L M2-HT | 100 - 130°F | | | | |
| 0274307 | 1 1/4" N 170-M2 | 130 - 180°F | | 0478024 | 1 1/4" N170-M3 | 90 - 180°F |
| 0274308 | 1 1/4" N 170L-M2 | 100 - 130°F | ⇒ | | | |
| 0478002 | 1 1/4" N 170M2-HT | 130 - 180°F | | | | |
| 0274322 | 1 1/4" N 170L M2-HT | 100 - 130°F | | | | |
| 0274311 | 1 1/2" N 170-M2 | 130 - 180°F | | 0478022 | 1 1/2" N170-M3 | 90 - 180°F |
| 0274312 | 1 1/2" N 170L-M2 | 100 - 130°F | ⇒ | | | |
| 0478003 | 1 1/2" N 170M2-HT | 130 - 180°F | | | | |
| 0274323 | 1 1/2" N 170L M2-HT | 100 - 130°F | | | | |
| 0274315 | 2" N 170-M2 | 130 - 180°F | | 0478027 | 2" N170-M3 | 90 - 180°F |
| 0274316 | 2" N 170L-M2 | 100 - 130°F | ⇒ | | | |
| 0478004 | 2" N 170M2-HT | 130 - 180°F | | | | |
| 0274324 | 2" N 170L M2-HT | 100 - 130°F | | | | |



USA: 815 Chestnut St., No. Andover, MA 01845-6098; www.watts.com
 Canada: 5435 North Service Rd., Burlington, ONT. L7L 5H7; www.wattscanada.ca



A Watts Water Technologies Company