

CARTRIDGE TANK® FILTRATION SYSTEM

The Blue Filtration Series incorporates surface modified carbon block filter technology that is highly effective reducing bad taste, odor, and the reduction of chlorine and chloramines from potable drinking water. The filters are made using high performance coconut shell carbon, which has more micropores compared to other types of carbon.

Coupled with a unique binder system, these carbon block filters deliver a product with superior adsorption capacity and kinetic dynamics. The unique high capacity filters provide cost effective water filtration solutions in a size and configuration that offer ease-of-use, extended service life and high capacity, with a low pressure loss.

The Chloramine Block is a proprietary media with an enormous number of catalytically active Nitrogen Groups for highly efficient reduction of chloramines. This enhanced catalytic functionality has FIVE times more capacity for chloramines reduction than standard carbon blocks.

All components and materials are made with FDA approved materials and Manufactured from NSF 61 Certified Coconut Shell carbon. Each filter comes with a unique handle designed top cap for lightweight and easy removal, a bag for proper disposal, and a double o-ring bottom connection into the **Cartridge Tank®** plumbing adapter for the 2½" assembly and full 1¼" PVC glue socket flow rate connections.

Available in three filter configurations:

SCT-03CB: 3 Micron Carbon Block, High Capacity

SCT-20CB: 20 Micron Carbon Block, High Porosity/ Low Pressure Drop

SCT-03CBAMINE: 3 Micron Carbon Block, Chloramine Reduction

Blue Filtration Series

Features

High-performance carbon

Unique binder system

Proprietary manufacturing process

Outer Wrap of Polypropylene

Netting of Polyethylene

Benefits

Exceptionally low pressure drop

High dirt holding capacity

Excellent contaminant reductions

Applications


Ideal for Residential, Food Service, Commercial and Industrial applications

Effective at reducing unwanted bad taste and odor, along with chlorine and chloramine taste and odor from potable drinking water

Ideal as polishing or pre-filters in applications requiring fine filtration and high capacity



Filter Performance



Blue Series Configuration

Item #: SCT-1/4NPTLID



Top Cap option with pressure release Valve & Removal Handles





Snap Ring with I.D. Tag connection.

Item #: SCT-2 5LID



2.5" Threaded top/bottom Res./LC Cap threaded connection.

Item #: SCT-2.5DRAIN SCT-2.5ADAPTER




2.5" Bottom Drain Plumbing for Res./LC Filters.

Better Filtration - There's No Competition

Nominal 3 micron (SCT-03CB) rated filter to treat >250,000 gallons (946,353 Liters) of water @ 15 gpm (56.78 LPM) with greater than 90% reduction, estimated capacity using 2ppm of free chlorine.

Nominal 20 micron (SCT-20CB) rated filter to treat >150,000 gallons (567,812 Liters) of water @ 7 gpm (26.50 LPM) with greater than 90% reduction, estimated capacity using 2ppm of free chlorine.

Nominal 3 micron Chloramine (SCT-03CBAMINE) rated filter to treat >50,000 gallons (189,271 Liters) of water @ 7 gpm (26.50 LPM) with greater than 85% reduction, estimated capacity.



Easy Replacements - No Tools Means No Tools

PRESS THE RED PRESSURE RELIEF VALVE & PULL SNAP-RING









Performance claims are based on independent lab results and manufacturer's internal test data. Actual performance is dependent on influent water quality, flow rates, system design and applications. Your results may vary. Micron ratings based on 85% or greater removal of a given particle size. Estimated capacity using 2ppm free chlorine with greater than 90% reduction. Flush new cartridges until water runs clear prior to use. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system



A Watts Water Technologies Company

USA: Tel. (800) 659-8400 • www.watts.com **Canada:** Tel. (888) 208-8927 • www.watts.ca